











NSTRUMENT CLUSTER



POWER STEERING



HIGHEST PTO POWER



MULTI DISC OUTBOARD OIB



DUAL CLUTCH



SPACIOUS PLATFORM



LIED Guidelights

Engine HP		SPECIFICATIONS -	4215E	
Engine HP			4WD	2WD
No. of Cylinders 3	Engine			
Rated RPM	Engine HP	10 ACCOMMENT	4	3
Max Torque (Nm) 196 Air Cleaner Dry Transmission Dual / Single* Gear Box 10F+5R Max Rated Speed (kmph) 37.2 Brake Brake Type Multi Disc Outboard OIB Hydraulics Lift Capacity (kg) 2000 Calt 3 Point Linkage Cat 2 Implements Hydraulic Control ADDC Steering Power Steering PTO PTO Standard RIPM 540 Tyre Front 8*18 6*16 Tyre Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	No. of Cylinders		3	
Air Cleaner	Rated RPM		18	00
Transmission Clutch Type Dual / Single*	Max Torque (Nm)			
Clutch Type Dual / Single* Gear Box 10F+5R Max Rated Speed (kmph) 37.2 Brake Brake Brake Type Multi Disc Outboard OIB Hydraulics Lift Capacity (kg) 2000 Calt 3 Point Linkage Cat 2 Implements Hydraulic Control ADDC Steering Power Steering PTO PTO PTO Standard RPM 540 Tyre Front 8*18 6*16 Tyre Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Air Cleaner		Dry	
Max Rated Speed (kmph) 37.2	Transmission			
Max Rated Speed (kmph) 37.2 Brake Brake Type Multi Disc Outboard OIB Hydraulics Lift Capacity (kg) 2000 Calt 3 Point Linkage Cat 2 Implements Hydraulic Control ADDC Steering Power Steering PTO POWER Steering PTO Standard RPM 540 Tyre Front 8*18 6*16 Tyre Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Clutch Type		Dual / Single*	
Brake Brake Type Multi Disc Outboard OIB	Gear Box		10F+5R	
Brake Type	Max Rated Speed (kmph)		37.2	
Lift Capacity (kg) 2000 Calt 3 Point Linkage	Brake			
Lift Capacity (kg) 2000 Calt 3 Point Linkage	Brake Type		Multi Disc Outboard OIB	
3 Point Linkage Cat 2 Implements				
ADDC				
Steering Power Steering	3 Point Linkage			
Power Steering Power Steering			AD	DC
PTO Standard RPM 540 Tyre Front 8*18 6*16 Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight Total Weight (kg) 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800				
PTO Standard RIPM 540 Tyre Front 8*18 6*16 Rear 13.6*28 13.6*28 13.6*28 13.6*2	Steering		Power	Steering
Tyre Front 8*18 6*16 Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight Total Weight (kg) 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	PTO			
Front 8*18 6*16			540	
Tyre Rear 13.6*28 13.6*28 Fuel Tank Capacity (L) 55 Dimensions & Weight Total Weight (kg) 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Tyre			
Rear 13.6*28 13.6*28 13.6*28	Tyre	Front	8*18	6*16
Capacity (L) 55 Dimensions & Weight 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800		Rear	13.6°28	13.6*28
Dimensions & Weight Total Weight (kg) 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Fuel Tank			
Total Weight (kg) 2280 2070 Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Capacity (L)		55	
Wheel Base (mm) 2080 1970 Length (mm) 3610 3620 Width (mm) 1840 1800	Dimensions & Weight			
Length (mm) 3610 3620 Width (mm) 1840 1800	Total Weight (kg)		2280	2070
Width (mm) 1840 1800	Wheel Base (mm)		2080	1970
	Length (mm)		3610	3620
pilons Available	Width (mm)		1840	1800
	Opilions Available			

- E3 Engine Curve (Fuel & Torque) designed by Japanese Experts.
- E3 Engine having Extra large size lending Extra Power, Torque and Pickup
- · Efficient fuel combustion which results in Extra Mileage, Extra engine life for trouble free operations



- · Digitally controlled precise and uniform depth of operations.
- Next Gen Hydraulic Control Valve designed by Japanese
- . Experts Automatic Hitch lowering and raising for easy mounting and dismounting implements
- . More comfort, saves time and money, increases productivity



- Easy Shift Speed Plus Gearbox for all range of applications
- Best in class Multi-Speed Transmission with 10+5 with Express speed gearbox
- Smooth gear shifting with Japanese Technology



- · Fully sealed 4WD Japanese Technology with Japanese Seals.
- . High ground clearance enables smooth & hurdle free operations
- . Turn plus Axle for Shorter turning radius with excellent maneuverability.
- · Best suited for Puddling and heavy applications.













*Since product upgradation is a confinuous process, specification and details provided are subject to change without any prior infimation. "Terms and condition apply.



INTERNATIONAL TRACTORS LIMITED

OFFICE: Plot No.10, Teri University, Vasant Kunj Institutional Area, Vasant Kunj, New Delhi-110070 | Tel: 91-11-66455200 MARKETING OFFICE: C-133A, Second Floor, Sector-2, Noida, U.P., India | Tel: 0120-4095860 | Email: support@solistractors.in PLANT: International Tractors Limited: Village Chak Gujran, P.O. Piplanwala Jalandhar Road, Hoshiarpur, Punjab-146022. Tel: 91-1882-522220, 522221 | Fax: 91-1882-522222 | Web: solis-yanmar.com