



DYNAMIC STYLING



INSTRUMENT
CLUSTER



LED
GUIDELIGHTS



SPACIOUS
PLATFORM




12+12 SOLIS
SHUTTLE SHIFT



6 STAGE
COOLING



HIGHEST
PTO POWER



POWER STEERING



DUAL CLUTCH



MULTI DISC
OUTBOARD OIB

5724 S
57HP_{CAT.}



JAPANESE
TECHNOLOGY
Engine Expert

JAPANESE
TECHNOLOGY
Transmission Expert

JAPANESE
TECHNOLOGY
Hydraulics
Expert

SPECIFICATION - SOLIS 5724 S

	2WD	4WD
Engine		
Engine Power HP (Cat)	57	
Cubic Capacity(cc)	4087	
No. of Cylinders	4	
Rated RPM	2000	
Max Torque (Nm)	230 Nm	
Air Cleaner	Dry	
Transmission		
Clutch Type	Dual/Double (Optional)	
Gear Box	12F+12R Planetary with Synchromesh Gears	
Max Speed @ Rated ERPM (kmph)	31.25	
Brake		
Brake Type	Multi Disc Outboard OIB	
Hydraulics		
Hydraulic Lift Capacity (Kg)	2500 Cat.	
3 Point Linkage	Cat 2 Implements	
Hydraulic Control	Hydrotronic ADDC Lift	
Steering		
Steering	Power Steering	
PTO		
PTO Standard RPM	540	
Reverse PTO	Yes	
IPTO	Yes	
Tyre		
Front	7.50*16	9.5*24
Rear	16.9*28	16.9*28
Fuel Tank Capacity		
Fuel Tank Capacity (L)	65	
Dimensions & Weights		
Total Weight (Kg)	2450	2815
Wheel Base (mm)	2210	2320
Overall Length (mm)	3760	3900
Overall Width (mm)	1990	1990

*Options Available

SPECIAL SOLIS SERIES

(SPECIAL TRACTOR FOR SPECIAL APPLICATION)

LOADER



GRADER



ROTAVATOR



Dealership stamp



*Since product upgradation is a continuous process, specification and details provided are subject to change without any prior intimation.
*Terms and condition apply.

SOLIS5724S / 022022 / ENGLISH

INTERNATIONAL TRACTORS LIMITED (Solis Tractors Division)

HEAD OFFICE: Plot No.10, Teri University, Vasant Kunj Institutional Area, Vasant Kunj, New Delhi-110070 | Tel: 91-11-66455200

MARKETING OFFICE: 1st Floor, Ambience Tower-3, Pocket B-C, Sector-A, Vasant Kunj, New Delhi-110070

PLANT: International Tractors Limited, Village Chak Gujran, P.O. Piplanwala Jalandhar Road, Hoshiarpur, Punjab-146022 | Tel: 91-1882-522220, 522221

9311397211 | Email: support@solistractors.in



1800 1200 76547
SOLIS

www.solis-yanmar.com