

**SOLIS COMMITTED TOWARDS**

**CLEANER & GREENER ENVIRONMENT**

MODEL NO.

**2547**

MODEL NO.

**888**



1800 1200 76547  
**SOLIS**

Model		2547	888
<b>TRACTOR REQUIREMENTS</b>			
PTO Power	hp	40 to 45	45 to 50
<b>PICK-UP</b>			
Working width	cm	160	205
Tine	n	64	110
Hydraulic lift		Yes	Yes
Feeding Fork		2 Fork	3 Fork
Opening	cm <sup>2</sup>	1640	1850
<b>PLUNGER ON BEARINGS</b>			
Strokes/minute	n/min	90	90
Stroke Length	cm	71	75
<b>KNOTTING SYSTEM</b>			
Knotters	n	2	2
Tying material		Twine	Twine
Knotted Fan		No	Yes
<b>OUTPUT BALES</b>			
Chamber	cm x cm	35x47	37x49
Adj. Length	cm	40-130	40-130
Bale Weight	kg	18-30	25-50
<b>BALER DIMENSIONS</b>			
Length	cm	443	487
Width	cm	238	286
Height	cm	153	156
Weight	kg	1250	1670
<b>TRANSMISSION</b>			
Type		Reinforced pinion and gear	Reinforced pinion and gear

## Advantages



Hydraulic Moving Draw Bar  
Saves Time & Effort



Bevel Gear Box  
Ease of Operation &  
Lower Maint. Cost



Heavy Duty Flywheel  
Smooth Transmission with  
Maximum Power



Hydraulically  
Adjustable Pick-Up Height  
Easy Operations



Longer Bale Chamber  
Highest Density Bales



Knotted Fan  
Complete Cleanliness Of  
Binding System



Four Way Bale  
Adjustment System



Auth. Dealer

## INTERNATIONAL TRACTORS LIMITED (SOLIS TRACTORS DIVISION)

Marketing Office: C-133A, Second Floor, Sector-2, Noida - 201301, U.P., India

Tel: 0120-4095860 | Email: support@solistractors.in | Website: www.solis-yanmar.com