


ADVANCED TRACTORS WITH THE WORLD'S BEST ENGINE.

YM SERIES













ADVANCED JAPANESE TECHNOLOGY

ZERO NOISE ZERO VIBRATION RENOWNED 100 YEAR OLD JAPANESE ENGINE TECHNOLOGY

4 cylinder 16 Valve Engine

with Monoplunger FIP

Underhood Exhaust System

Balancer Shaft to eliminate Noise and Vibration

FULLY SEALED 4WD FRONT AXLE

» Turn Plus Technology

» High Ground Clearance (425 mm)



» Shuttle Lever with Finger Touch Operation

» Planetary Gear-Drive

TOP END COMFORT AND SAFETY FEATURES



Dynamic Styling and Projector Lamps



Neutral Safety Switch and Differential Lock



Seat Belt and ROPS



Lightweight and Fully Sealed Tractor

TECHNICAL SPECIFICATIONS

Models		YM 348A	YM 342A
Engine	Engine Power HP (Cat)	48	42
	Cubic capacity (CC)	3054	2190
	Rated RPM	2100	2500
	Max Torque (Nm)	207.4	142.9
	No. of Cylinders	4	4
	Air Cleaner	Dry	Dry
Transmission	Transmission type	Synchro-Reverser	Synchro-Reverser
	Gear Box speeds	8F + 8R	8F + 8R
	Max Speed @ Rated ERPM	29.78	29.29
Brake	Brake Type	OIB	OIB
Hydraulics	Hydraulic Lift Capacity (Kg)	1450	1450
	3 Point Linkage	CAT2 / CAT1	CAT2 / CAT1
	Hydraulic Control	Hydrotronic ADDC	Hydrotronic ADDC
Steering	Steering	Power Steering	Power Steering
РТО	PTO Standard RPM	540/540E	540/540E
	IPTO	Yes, with Ergo Knob	Yes, with Ergo Knob
Tyre	Front	8.00*18	8.00*18
	Rear	13.6*28	13.6*28
Dimensions & Weights	Total Weight (Kg)	1960	1850
	Wheel Base (mm)	1970	1900
	Overall Length (mm)	3562	3531
	Overall Width (mm)	1618	1618
	Ground Clearance (mm)	425	425

Note: All technical data, measurement and weight are approximate, and the manufacturer has the right to make alteration without prior notice.



